PRODUCT DATA SHEET

YOLO Colorhouse Inside – Eggshell Finish	111219

- **ZERO VOC**
- **LOW ODOR**
- **DURABLE AND WASHABLE**
- **FAST DRYING**
- **WATER CLEAN-UP**
- **SELECT DESIGNER PALETTE**

YOLO Colorhouse® began with the elemental – what to put into our paint and what to leave out. With 40% volume solids and Green Seal™ certification, YOLO Colorhouse performs like a premium conventional paint, yet it has low odor, no harmful chemicals, and no added solvents. YOLO Colorhouse is a premium, 100% acrylic paint with excellent hide and durability.

USAGE A zero VOC, low odor, eggshell finish for interior use.

AVAILABILITY Quarts, Gallons, and Five gallon containers.

COVERAGE 400 sq. feet per gallon.

DRY TIME At 77°F and 50% humidity: dry time to touch is 30 min. and dry time to re-coat is 2 hours.

SURFACE PREPARATION Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, wax, and mildew. Remove peeling paint or loose material on surface*. Glossy surfaces must be dulled or primed for best results. For new wallboard, thoroughly vacuum fine dust from walls. Use YOLO Colorhouse Inside Primer for new wallboard, new wood, cured masonry and plaster, spackled areas, and when going from a dark to light color. New plaster or masonry must be allowed to cure 30-60 days before priming. If previously painted with latex, no priming is necessary. Do not paint on unprimed metal.

*Warning!: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION Mix paint thoroughly before use. Keep lid on can of unused portion to prevent skinning. Apply with brush to cut-in edges and roller to roll wall surfaces. For brushing, use a high-quality brush. For rolling, use ⅜" to ¾" nap roller cover. For airless sprayer – no thinning is recommended, 2000–2500 PSI, tip – .015"-.021". For conventional sprayer and HVLP, reduce up to 1 pint per gallon with clean water. NOT recommended for cabinets or furniture.

CLEAN UP Remove excess paint from equipment before washing with water.

THINNING Thinning is not recommended.

DISPOSAL Check www.earth911.org for recycling and disposal information in your area. Do not pour unused contents down drain. Pour into absorbent material, let dry and dispose with trash – OR take to hazardous waste collection program.

PHYSICAL PROPERTIES

Viscosity range: 102 ± 2 KU

Solids Volume: 40 ± 2

Solids Weight: 53 ± 2

Odor: No toxic or offensive odor during painting, no odor once dried

Toxic Properties: Non-toxic

Weight: 11.1 lbs. per gallon

Theoretical VOC: Zero

Gloss: 60° – 8-12 (Eggshell)

LIMITATIONS Do not apply when surface or air temperatures are expected to drop below 50°F (10°C) or rise above 95°F (35°C) during application and drying. Keep from freezing. Do not apply to unprimed metal surfaces.

Disclaimer: All technical advice, recommendations, and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice, or services are not to be taken as a license to operate under or suggest infringement of any patient.

www.yolocolorhouse.com

© 2007 YOLO Colorhouse® is a registered trademark of YOLO Colorhouse LLC.

116 SE Yamhill Street
Portland, OR 97214
503-493-8275